

 SHARE

Compact Track Loaders / T870 Compact Track Loader

Specifications & Options

Standard	Optional	Not Applicable	Units	US
Bobcat T870				
Engine				
				Tier 4
				Liquid
				Diesel
				100 hp
Performance				
				3,650 lb
				5215 lb
				10430 lb
				12925 lb
				7.2 mph
				11.4 mph
				4.8 psi
Capacities				
				32.6 gal
Hydraulic System				
				3,500 psi
				23 gal/min
				36.6 gal/min

Dimension

Length	153.9 in
Length without Attachment	119.3 in
Length with Standard Bucket	153.9 in
Width	82.8 in
Width (with bucket)	84.8 in
Height	83.6 in
Height with Operator Cab	83.6 in
Height to Bucket Hinge Pin	144 in
Reach @ Maximum Height	36.5 in
Turning Radius	99 in
Length of track on ground	70.2 in
Track Width	17.7 in

Features

Joystick Control
 Air Conditioning
 Backup Alarm
 BICS System (Interlock)
 Cab Heater
 Operating Lights
 Suspension Seat
 Two Speed Travel
 Deluxe Instrumentation
 Engine Shutdown
 Hydraulic Bucket Positioning
 High Flow Option
 Auxiliary Hydraulics
 Bob-Tach Attachment System

 Power Bob-Tach

 ACS (Switchable Controls)
 Ride Control
 Horn

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.