




# AQUASTORM

**DESCRIPTION:** Paver **TEXTURE:** Smooth

## PALLET OVERVIEW



Aqua Storm paver meet and exceeds the requirements of ASTM C1319 for Concrete Grid Paving Units.

## NOTES

See page 62 to 64 for more technical information. When used in a permeable pavement application, see page 33 and 101 for more technical information.

See page 30 for more information about applications.

**JOINT WIDTH:** 1 5/8" (41 mm)  
**% OF SURFACE OPENING:** 38 %  
**INFILTRATION RATE:** 2 395 in./hr  
 (60 842 mm/hr)

## WINTER CONDITIONS


De-icing salts should never be used on grass as salt will damage it. The snowblower blade should be set to leave a 3/4 to 1 1/2 in. (2 to 4 cm) tamped snow cover to protect the grass from extreme cold and prevent it from being torn off during snow removal.

Specifications per pallet		Imperial	Metric
Cubing		<b>78.39 ft<sup>2</sup></b>	7.28 m <sup>2</sup>
Approx. Weight		2 245 lbs	1 018 kg
Number of rows		7	
Coverage per row		11.20 ft <sup>2</sup>	1.04 m <sup>2</sup>
Linear coverage per row	Depth	13.39 lin. ft	4.08 lin. m
	Length	6.69 lin. ft	2.04 lin. m




Unit dimensions	in	mm	Units/pallet
Height	3 15/16	100	56 units
Width	10 1/16	255	
Length	20 1/16	510	


01 | Linear pattern




02 | Linear pattern



03 | Herringbone pattern



04 | Herringbone pattern



Patterns are for design inspiration only. The installer is responsible to calculate & purchase the correct amount of material.

Grey



Grey

