




MISTA RANDOM

DESCRIPTION: Paver **TEXTURE:** Multi-textured

PALLET OVERVIEW



Permeable pavers allow for storm water drainage and manage excess runoff. The use of permeable pavers also facilitates LEED® certification easier to obtain.

NOTES

See page 62 to 64 for more technical information. When used in a permeable pavement application, see page 33 and 101 for more technical information.







See page 30 for more information about applications.

JOINT WIDTH: 3/16" TO 9/16" (4 TO 14 mm)


% OF SURFACE OPENING: 6.3%

INFILTRATION RATE: 610 in./hr
(15 505 mm/hr)


Specifications per pallet	Imperial	Metric
Cubing	116.20 ft²	10.80 m ²
Approx. Weight	3 356 lbs	1 522 kg
Number of rows	10	
Coverage per row	11.62 ft ²	1.08 m ²
Linear coverage per row	17.71 lin. ft	5.40 lin. m

	Unit dimensions	in	mm	Units/pallet
	Height	2 9/16	65	80 units
	Width	7 7/8	200	
	Length	3 15/16	100	
	Height	2 9/16	65	100 units
	Width	7 7/8	200	
	Length	7 7/8	200	
	Height	2 9/16	65	90 units
	Width	7 7/8	200	
	Length	11 13/16	300	


04 | Modular pattern



05 | Modular pattern



06 | Linear pattern



Patterns are for design inspiration only. The installer is responsible to calculate & purchase the correct amount of material.

Chestnut Brown



Sandlewood



Champlain Grey



Shale Grey

